

# RLC CIRCUIT

The **voltage** ( $V_C$ ) across the capacitor is given by:

The voltage ( $V_C$ ) across the capacitor is given by

$$V_C = \frac{V_T X_C}{(X_L - X_C)}$$

During resonant interaction, the incoming **unipolar pulse-train** (h) of Figure (1-1) as to Figure (9B) produces an step-charging voltage-effect across **Excitor-Array** (ER of t), as illustrated in Figure progressive function.




Figure 1-1




Figure 9B

Once the voltage-pulse is terminated or shut-off, voltage potential returns to an "ground-state" or near ground-state to start the voltage deflection process over again.

Voltage intensity or level across **Excitor-Array** (ER of t) can exceed 20,000 volts due to **circuit** (AA) interaction and is directly related to **pulse-train** (h) variable amplitude input.

## RLC CIRCUIT

**Inductor** (c) is made of or composed of **resistive wire** (R7) to further restrict D.C. current flow beyond **inductance reaction** ( $X_L$ ), and is given by

$$Z = \sqrt{R_I^2 + (X_L - X_C)^2}$$

## Dual-inline RLC NETWORK

Variable **inductor-coil** (y), similar to **inductor** (c) connected to **opposite polarity voltage zone** (E4) further inhibits electron movement or deflection within the Voltage Intensifier Circuit.

Moveable wiper arm fine "tunes" "**Resonant Action**" during pulsing operations.

**Inductor** (y) in relationship to **inductor** (c) electrically balances the opposite voltage electrical potential across voltage zones (E3/E4).

## VIC RESISTANCE

Since **pickup coil** (n) is also composed of or made of **resistive wire-coil** (R4), then, total circuit resistance is given by

$$Z = R_I + Z_2 + Z_3 + R_E$$

Where,  $R_E$  is the dielectric constant of **Argon** (Ar).

---

Revision #3

Created 2024-10-26 15:29:26 UTC by Chris Bake

Updated 2024-10-26 15:40:05 UTC by Chris Bake